

# Wet/Dry Vacuum

## - durable cleaning for rugged environments

The versatile Eliminator Pro II is designed to withstand regular use in rugged applications, while maintaining strong performance, suction and filtration.

### Features and Benefits

- 12-gallon collection container with drain hose for easy disposal of wet material
- Multi-stage filtration with dust bag (optional), washable main filter and upstream HEPA filter extend life of the vacuum
- Efficient bypass motor ensures minimal maintenance upkeep
- Optional fixed floor nozzle kit with squeegee available for collection of wet debris on smooth floors

### Standard Accessories Include:

8.2 ft. hose assembly, stainless steel extension wand (2 piece), floor nozzle with brush, floor nozzle with squeegee, crevice nozzle and round brush.



### Technical Specifications

Description	Unit	Eliminator Pro II
Collection Type	-	Wet/Dry
Type of Power	-	1-Phase
Voltage @ 60 Hz	V	120
Power @ 60 Hz, max.	HP (W)	1.3 (1000)
Waterlift, max.	in. (mm) H <sub>2</sub> O	89 (2260)
Airflow, max.	CFM (L/min)	130 (3681)
Current, max.	amps	8.5
Bag Capacity	gallons (L)	7.25 (27)
Tank Capacity	gallons (L)	12 (45)
Main Filter Area	ft <sup>2</sup> (m <sup>2</sup> )	1.45 (0.13)
HEPA Filter Area, upstream	ft <sup>2</sup> (m <sup>2</sup> )	6.99 (0.65)
HEPA Filter Efficiency	-	99.97% @ 0.3 μ
Machine Inlet Diameter	mm	58
Dimensions (L x W x H)	in. x in. x in. (mm x mm x mm)	26.5 x 17.25 x 36.5 (673 x 438 x 927)
Weight	lbs. (kg)	35 (16)
Cord Length	ft. (m)	50 (15)
Sound Pressure Level @ 3' 3"	dB(A)	66.7

Specifications and details are subject to change without prior notice.



Tilting motor head

### Nilfisk, Inc., Industrial Vacuum Division

740 Hemlock Rd. · Morgantown, PA · 19543  
 Tel.: (800) 645-3475 · Fax: (888) 624-8141  
 questions@nilfisk.com  
 www.nilfiskindustrialvacuums.com