

# Special Application Close Coupled Pump Three Phase Open Dripproof (ODP) NEMA<sup>®†</sup> Premium Efficient


**NEMA  
Premium**

DE1

## APPLICATIONS:

For the specific requirements of centrifugal pumps where the pump impeller is mounted directly on the motor shaft.  
Used where dirt and moisture are minimal.

## FEATURES:

- Class F Insulation, Class B Rise At Service Factor
- Rolled Steel Frame
- Aluminum End Shields 140-250, Cast Iron End Shields 280-320
- Oversized Ball Bearings w/Locked Shaft End Construction
- Premasked Mylar Nameplate (with "CE" Mark)
- F1 Assembly Position
- Regreaseable Bearings 180 Frame & Up, Lifting Provisions 210 Frame & Up
- Double Shielded Bearings
- 40°C Ambient, NEMA<sup>®†</sup> Design B Performance On 60 Hertz Sine Wave Power
- "JM" Shaft For Mechanical Seal
- "JM" Shaft on 210 Frame and Smaller; "JP" Shaft on 250 and 280 Frame
- Conversion Kits: Canopy Kits

## JM Shaft - Footed

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs)	NEMA Nom. Eff.	Full Load Amps	Notes
3/4	1200	208-230/460	143JM	DJ34P3DM	\$655	DS-3POP	1.15	15.4	30	80.0	2.8-2.8/1.4	03
1	1800	200	143JM	DJ1P2HM	\$487	DS-3POP	1.15	15.4	30	85.5	3.6	
	1800	208-230/460	143JM	DJ1P2DM	\$487	DS-3POP	1.15	15.4	30	85.5	3.1-3.1/1.5	03
	1200	208-230/460	145JM	DJ1P3DM	\$655	DS-3POP	1.15	15.4	35	82.5	4-4/2	03
1 1/2	1800	200	145JM	DJ32P2HM	\$513	DS-3POP	1.15	14.8	35	86.5	4.8	
	3600	208-230/460	143JM	DJ32P1DM	\$519	DS-3POP	1.15	15.4	30	85.5	4.2-3.8/1.9	03
	1800	200	145JM	DJ32P2HM	\$513	DS-3POP	1.15	14.8	35	86.5	4.8	03
	1800	208-230/460	145JM	DJ32P2DM	\$513	DS-3POP	1.15	14.8	35	86.5	4.4-4.1/2.1	03
	1200	208-230/460	182JM	DJ32P3DM	\$660	DS-3POP	1.15	16.0	50	86.5	5.2-5.3/2.6	03
2	3600	208-230/460	145JM	DJ2P1DM	\$567	DS-3POP	1.15	15.4	35	85.5	5.5-5/2.5	03
	1800	200	145JM	DJ2P2HM	\$563	DS-3POP	1.15	15.4	35	86.5	6.3	
	1800	208-230/460	145JM	DJ2P2DM	\$563	DS-3POP	1.15	14.8	35	86.5	5.9-5.6/2.8	03
	1800	575	145JM	DJ2P2GM	\$563	DS-3POP	1.15	15.34	35	86.5	2.2	
	1200	208-230/460	184JM	DJ2P3DM	\$739	DS-3POP	1.15	16.0	60	87.5	6.4-6.3/3.1	03
3	3600	208-230/460	145JM	DJ3P1DM	\$582	DS-3POP	1.15	15.4	35	85.5	8.3-7.4/3.7	03
	1800	200	182JM	DJ3P2HM	\$598	DS-3POP	1.15	17.4	50	89.5	9	
	1800	208-230/460	182JM	DJ3P2DM	\$598	DS-3POP	1.15	16.0	50	89.5	8.3-7.7/3.8	03
	1200	208-230/460	213JM	DJ3P3DM	\$941	DS-3POP	1.15	17.8	90	88.5	9.4-8.9/4.5	
5	3600	200	182JM	DJ5P1HM	\$620	DS-3POP	1.15	17.4	50	88.5	14.1	
	3600	208-230/460	182JM	DJ5P1DM	\$620	DS-3POP	1.15	16.1	50	88.5	13.5-12.3/6.2	
	1800	200	184JM	DJ5P2HM	\$645	DS-3POP	1.15	20.5	60	89.5	14.7	
	1800	208-230/460	184JM	DJ5P2DM	\$645	DS-3POP	1.15	16.0	60	89.5	13.7-12.4/6.2	03
	1800	575	184JM	DJ5P2GM	\$645	DS-3POP	1.15	16.0	60	89.5	4.9	
	1200	208-230/460	215JM	DJ5P3DM	\$1,234	DS-3POP	1.15	19.3	105	89.5	15.2-14.5/7.3	
7 1/2	3600	208-230/460	184JM	DJ7P1DM	\$968	DS-3POP	1.15	17.4	60	88.5	20.5-18.1/9.1	03
	1800	200	213JM	DJ7P2HM	\$943	DS-3POP	1.15	17.8	90	91.0	21.4	
	1800	208-230/460	213JM	DJ7P2DM	\$943	DS-3POP	1.15	17.8	90	91.0	20.2-18.5/9.3	03
	1800	575	213JM	DJ7P2GM	\$943	DS-3POP	1.15	17.8	90	91.0	7.3	

Note 03 660/50 Hz rated with no derate on HP; 230/460 volt 60 Hz ratings operate on 190/380 volt 50 Hz; 460V 60 Hz ratings operate on 380V 50 Hz; Full 60 & 50 Hz data on Nameplate

† All marks shown within this document are properties of their respective owners.



# Special Application Close Coupled Pump Three Phase Open Dripproof (ODP) NEMA<sup>®†</sup> Premium Efficient



**NEMA**  
Premium

DE1

(continued)

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs)	NEMA Nom. Eff.	Full Load Amps	Notes
10	3600	200	213JM	DJ10P1HM	\$1,132	DS-3POP	1.15	17.8	90	90.2	28	03
	3600	208-230/460	213JM	DJ10P1DM	\$1,132	DS-3POP	1.15	17.8	90	90.2	27.1-24.3/12.2	03
	3600	575	213JM	DJ10P1GM	\$1,132	DS-3POP	1.15	17.78	90	90.2	9.7	
	1800	200	215JM	DJ10P2HM	\$1,147	DS-3POP	1.15	19.3	105	91.7	28.1	03
	1800	208-230/460	215JM	DJ10P2DM	\$1,147	DS-3POP	1.15	19.3	105	92.4	26.3-23.8/11.9	03
15	3600	208-230/460	215JM	DJ15P1DM	\$1,555	DS-3POP	1.15	19.3	105	90.2	40-36/18	03
	1800	208-230/460	254JM	DJ15P2DM	\$1,712	DS-3POP	1.15	24.6	160	93.0	40-36/18.2	
20	3600	208-230/460	254JM	DJ20P1DM	\$1,874	DS-3POP	1.15	24.6	170	91.7	52-46/23.1	
	3600	575	254JM	DJ20P1GM	\$1,874	DS-3POP	1.15	24.6	170	91.0	18.7	
	1800	208-230/460	256JM	DJ20P2DM	\$1,970	DS-3POP	1.15	25.2	195	93.0	54-49/24.4	
25	3600	208-230/460	256JM	DJ25P1DM	\$2,567	DS-3POP	1.15	25.2	200	91.7	65-57/28.7	
	1800	208-230/460	284JM	DJ25P2DM	\$2,435	DS-3POP	1.15	25.8	225	93.6	64-58/29	03
30	3600	208-230/460	284JM	DJ30P1DM	\$2,901	DS-3POP	1.15	25.8	225	92.4	79-68/34	03
	1800	208-230/460	286JM	DJ30P2DM	\$2,892	DS-3POP	1.15	25.8	250	94.1	77-69/34	03
40	3600	208-230/460	286JM	DJ40P1DM	\$3,171	DS-3POP	1.15	25.8	250	93.0	104-90/45	03
	3600	575	286JM	DJ40P1GM	\$3,171	DS-3POP	1.15	25.8	250	93.0	36	
	1800	208-230/460	324JM	DJ40P2DM	\$3,178	DS-3POP	1.15	27.5	385	94.1	102-91/46	03
50	3600	208-230/460	324JM	DJ50P1DM	\$3,567	DS-3POP	1.15	27.5	385	93.0	130-117/59	03
	1800	208-230/460	326JM	DJ50P2DM	\$3,725	DS-3POP	1.15	27.5	460	94.5	126-113/56	03
60	3600	208-230/460	326JM	DJ60P1DM	\$4,916	DS-3POP	1.15	27.5	460	93.6	152-134/67	03

## JM Shaft - Footless

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs)	NEMA Nom. Eff.	Full Load Amps	Notes
1	1800	208-230/460	143JM	DJ1P2DU	\$570	DS-3POV	1.15	15.6	30	85.5	3.2-3.1/1.6	03,NNP
1 1/2	3600	208-230/460	143JM	DJ32P1DU	\$609	DS-3POV	1.15	15.6	30	85.5	4.2-3.8/1.9	03,NNP
	1800	208-230/460	145JM	DJ32P2DU	\$581	DS-3POV	1.15	15.6	35	86.5	4.4-4.2/2.1	03,NNP
2	1800	208-230/460	145JM	DJ2P2DU	\$642	DS-3POV	1.15	15.6	35	86.5	5.9-5.6/2.8	03,NNP
3	1800	208-230/460	182JM	DJ3P2DU	\$758	DS-3POV	1.15	17.1	50	89.5	8.3-7.7/3.8	03,NNP
5	1800	208-230/460	184JM	DJ5P2DU	\$898	DS-3POV	1.15	17.1	60	89.5	13.7-12.4/6.2	03,NNP
7 1/2	1800	208-230/460	213JM	DJ7P2DU	\$1,188	DS-3POV	1.15	18.6	90	91.0	20.2-18.5/9.3	03,NNP
10	3600	208-230/460	213JM	DJ10P1DU	\$1,420	DS-3POV	1.15	18.6	90	90.2	27.1-24.3/12.2	03,NNP
	1800	208-230/460	215JM	DJ10P2DU	\$1,400	DS-3POV	1.15	18.8	105	91.7	26.2-23.7/11.9	03,NNP
15	3600	208-230/460	215JM	DJ15P1DU	\$1,809	DS-3POV	1.15	18.8	105	90.2	40-36/18	03,NNP
	1800	208-230/460	254JM	DJ15P2DU	\$2,055	DS-3POV	1.15	25.5	160	93.0	40-36/18.2	NNP
20	3600	208-230/460	254JM	DJ20P1DU	\$2,249	DS-3POV	1.15	25.5	160	91.7	52-46/23.1	NNP

Note 03 660/50 Hz rated with no derate on HP; 230/460 volt 60 Hz ratings operate on 190/380 volt 50 Hz, 460V 60 Hz ratings operate on 380V 50 Hz; Full 60 & 50 Hz data on Nameplate

Note NNP Non-NEMA<sup>®†</sup> Premium

† All marks shown within this document are properties of their respective owners.



BRAKEMOTORS  
GENERAL PURPOSE SINGLE PHASE  
HVAC  
WASHDOWN  
AGRICULTURE  
COMMERCIAL PUMP MOTORS  
CLOSE COUPLED PUMP MOTORS  
FIRE PUMP MOTORS  
POOL & SPA MOTORS  
RESIDENTIAL WATER PUMP  
ELEVATOR GATE & DOOR  
VARIABLE SPEED MOTORS AND DRIVES