

Permanent Split Capacitor Condenser Fan 5.0" Diameter, Totally Enclosed Air Over (TEAO)



APPLICATIONS:

Residential condensing unit fan motor.

FEATURES:

- 42" Leads
- Shaft Down Mount
- #8-32 Studs
 - Fig A: 4.312" Diameter Bolt Circle
 - Fig B: 4.464" Diameter Bolt Circle
- Suitable For Use with 370V Capacitor
- 1/2" Diameter Shaft with Flat
- Reversible Rotation
- Automatic Reset Thermal Overload Protector
- **Discount Symbol DS-3HAC**




Figure A




Figure B

"Clam Shell" Single Speed, Stud Mount, Without Capacitor (Fig A) 4.312" Bolt Circle

HP	RPM	Voltage	Catalog Number	List	Bearings	Cap. MFD	Amps	Shaft N	Shell XI	Total C	Ship Wt. (lbs)	Notes	OEM
1/10	1075	208-230	2243	\$124	SAB	5.0	0.75	2.7	4.1	6.8	9		
1/8	1075	208-230	2249	\$126	SAB	5.0	0.90	2.7	4.1	6.8	10		
1/5	1075	208-230	2246	\$127	SAB	5.0	1.60	2.7	4.1	6.8	10		
1/4	1075	208-230	2250	\$128	SAB	7.5	1.70	2.7	4.1	6.8	10		

5.0" Single Speed, Stud Mount, Without Capacitor (Fig B) 4.464" Bolt Circle

HP	RPM	Voltage	Catalog Number	List	Bearings	Cap. MFD	Amps	Shaft N	Shell XI	Total C	Ship Wt. (lbs)	Notes	OEM
1/20	1550	230	1989P	\$201	SAB	3.0	1.3	2.5	3.8	6.3	8	H35,H42	CO
1/8	1550	208-230	1176	\$291	Ball	5.0	1.1	2.8	3.7	6.4	7	H36	BO
1/6	1075	208-230	1901	\$178	SAB	5.0	1.0	2.0	3.8	5.8	11		LE

BO = Bohn^{®†} CO = Copeland^{®†} LE = Lennox^{®†}

Note H35 Open Air Over
 Note H36 Open Dripproof
 Note H42 Shaft Down

† All marks shown within this document are properties of their respective owners.

