

General Purpose Three Phase Open Dripproof (ODP) NEMA® Premium Efficient – IE3



**NEMA
Premium**

DE, RE

(continued)

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	NEMA Nom. Eff.	Full Load Amps	Notes
2	3600	208-230/460	56H	D2S1AH	\$401	DS-3E	1.15	11.9	32	82.5	6.0-5.4/2.7	26, NNP LA
	3600	575	145T	D2P1G	\$515	DS-3E	1.15	12.8	35	85.5	2	
	1800	200	145T	D2P2H	\$512	DS-3E	1.15	12.8	35	86.5	6.4	
	1800	208-230/460	145T	D2P2D	\$512	DS-3E	1.15	12.8	35	86.5	5.9-5.6/2.8	3
	1800	208-230/460	56H	D2P2AH	\$415	DS-3E	1.15	12.9	40	86.5	6.6-6.6/3.3	26
	1800	208-230/460	56HZ	D2E2DHZ	\$383	DS-3E	1.15	12.5	26	85.5	6.6-6.6/3.3	26, NNP
	1800	208-230/460	56HZ	D2P2DHZ	\$444	DS-3E	1.15	14.3	26	86.5	6.2-6.0/3.0	26
	1800	230/460	145T	D2P2B2	\$512	DS-3E	1.15	12.8	35	86.5	5.4/2.7	05,26
	1800	575	145T	D2P2G	\$512	DS-3E	1.15	12.8	35	86.5	2.2	
	1200	200	184T	D2P3H	\$672	DS-3E	1.15	15	60	87.5	7.3	
	1200	208-230/460	184T	D2P3D	\$672	DS-3E	1.15	13.7	60	87.5	6.4-6.3/3.1	3
	1200	575	184T	D2P3G	\$672	DS-3E	1.15	15	60	87.5	2.5	
900	208-230/460	213T	D2E4D	\$1,057	DS-3E	1.15	16	94	85.5	7.9-7.4/3.7	03, NNP	
900	575	213T	D2E4G	\$1,057	DS-3E	1.15	16	90	85.5	2.9	NNP	
3	3600	200	145T	D3P1H	\$529	DS-3E	1.15	12.8	35	85.5	8.4	
	3600	208-230/460	145T	D3P1D	\$529	DS-3E	1.15	12.8	35	85.5	8.3-7.4/3.7	3
	3600	575	145T	D3P1G	\$529	DS-3E	1.15	12.8	35	85.5	2.9	
	1800	200	182T	D3P2H	\$544	DS-3E	1.15	13.7	50	89.5	8.8	
	1800	208-230/460	182T	D3P2D	\$544	DS-3E	1.15	13.7	50	90.2	8.3-7.6/3.8	3
	1800	208-230/460	182T	D3PA2D	\$794	DS-3E	1.15	15	50	89.5	8.4-7.9/3.9	24
	1800	208-230/460	56HZ	D3P2AHZ	\$576	DS-3E	1.15	13.5	21	86.9	9.7-9.4/4.6	26
	1800	575	182T	D3P2G	\$544	DS-3E	1.15	13.7	50	89.5	3.1	
	1200	200	213T	D3P3H	\$855	DS-3E	1.15	16	90	88.5	10.5	
	1200	208-230/460	213T	D3P3D	\$855	DS-3E	1.15	16	94	89.5	9.4-8.8/4.4	
	1200	575	213T	D3P3G	\$855	DS-3E	1.15	16	90	88.5	3.6	
	900	208-230/460	215T	D3E4D	\$1,355	DS-3E	1.15	17.5	104	86.5	11.6-10.8/5.4	03, NNP
900	575	215T	D3E4G	\$1,355	DS-3E	1.15	17.5	100	86.5	4.4	NNP	
5	3600	208-230/460	182T	D5P1D	\$564	DS-3E	1.15	13.7	50	88.5	13.5-12.3/6.2	3
	3600	200	182T	D5P1H	\$564	DS-3E	1.15	13.7	50	88.5	14.1	
	3600	208-230/460	182T	D5P1D	\$564	DS-3E	1.15	15	50	89.5	13.5-12.3/6.2	3
	3600	575	182T	D5P1G	\$564	DS-3E	1.15	13.7	50	87.5	5	
	1800	200	184T	D5P2H	\$586	DS-3E	1.15	13.7	70	89.5	14.2	
	1800	208-230/460	184T	D5P2D	\$586	DS-3E	1.15	13.7	70	89.5	13.7-12.4/6.2	3
	1800	208-230/460	184T	D5PA2A	\$836	DS-3E	1.15	15	68	89.5	13.8-12.6/6.3	24,26
	1800	575	184T	D5P2G	\$586	DS-3E	1.15	13.7	70	89.5	4.9	
	1200	200	215T	D5P3H	\$1,122	DS-3E	1.15	17.5	100	89.5	16.1	
	1200	208-230/460	215T	D5P3D	\$1,122	DS-3E	1.15	17.5	104	89.5	15.2-14.5/7.3	
	1200	575	215T	D5P3G	\$1,122	DS-3E	1.15	17.5	100	89.5	5.7	
	900	208-230/460	254T	D5E4D	\$1,737	DS-3E	1.15	22.6	162	88.5	16.2-15.2/7.6	02,03, NNP
900	575	254T	D5E4G	\$1,737	DS-3E	1.15	22.6	150	87.5	6.2	02, NNP	
7 1/2	3600	200	184T	D7P1H	\$880	DS-3E	1.15	13.7	60	88.5	20.8	
	3600	208-230/460	184T	D7P1D	\$880	DS-3E	1.15	13.7	60	88.5	20.3-18.1/9.1	3
	3600	575	184T	D7P1G	\$880	DS-3E	1.15	13.7	60	88.5	7.3	
	1800	200	213T	D7P2H	\$857	DS-3E	1.15	16	94	91	21.4	
	1800	208-230/460	213T	D7P2D	\$857	DS-3E	1.15	16	105	91	20.2-18.5/9.3	
	1800	208-230/460	213T	D7PA2A	\$1,207	DS-3E	1.15	16	90	91	20.5-18.5/9.2	24,26
	1800	575	213T	D7P2G	\$857	DS-3E	1.15	16	94	91	7.3	
	1200	200	254T	D7P3H	\$1,423	DS-3E	1.15	22.6	150	91	21.9	NNP
	1200	208-230/460	254T	D7P3D	\$1,423	DS-3E	1.15	22.6	150	91	20.5-18.9/9.5	02,03
	1200	575	254T	D7P3G	\$1,423	DS-3E	1.15	22.6	150	91	7.6	2
900	208-230/460	256T	D7E4D	\$2,210	DS-3E	1.15	23.2	172	88.5	23.9-22.8/11.4	02,03, NNP	

† All marks shown within this document are properties of their respective owners.



Revised – February 2016

GENERAL PURPOSE UNIMOUNT
GENERAL PURPOSE STEEL EDGE™
GENERAL PURPOSE HOSTILE DUTY
GENERAL PURPOSE CORRO-DUTY™
GENERAL PURPOSE 841 PLUS®
GENERAL PURPOSE OPEN DRIPPROOF
GENERAL PURPOSE HAZARDOUS LOCATION
GENERAL PURPOSE AUTOMOTIVE DUTY
COOLING TOWER DUTY
HAZARDOUS LOCATION
C-FACE MOTORS
VARIABLE FREQUENCY